

Instructions for Installing a Door Brush

Controlled ventilation helps reduce condensation and damp, by letting fresh air in when needed. However, draughts are uncontrolled - they let in too much cold air and waste too much heat.

To draught-proof your home you should block up unnecessary gaps that let cold air in and warm air out. Installing a door brush means you'll use less energy to heat your home, so you'll save money as well as making your home snug and pleasant.

1. Measure the width of the door.
2. Slide the brush insert from its housing.
3. Mark the housing to the width of the door.
4. Cut the housing to size using the hacksaw.
5. Use the pliers to cut the brush insert to the same width as the housing.
6. Slide the brush back into the main housing.
7. Place the brush against the door, ensure the gap is covered but that the door can open without the brush dragging.
8. With a bradawl, mark the holes at each fixing point.
9. Use the screws provided to fix the brush to the door.

Tools required:

Tape Measure

Pencil

Hacksaw

Pliers

Bradawl

Screwdriver



Please note: If you experience any difficulty fitting this product, please call LEAP's dedicated Installation Helpline on 0800 029 4549 to speak to an energy advisor who will give further guidance and assistance over the telephone* This service is open weekdays 8.45am to 5.30pm.

** this is a helpline service only and it is not possible to arrange for an energy advisor to visit your home to assist.*